

FTPC30V-E series

30W Constant Voltage LED Power Supply



■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Over current / Over voltage
- Cooling by free air convection
- Compliance to worldwide regulations for lighting



© ELECTRICAL SPECIFICATION

MODEL	FTPC30V12-E	FTPC30V24-E
OUTPUT		
Rated Voltage	12V	24V
Rated Current	2.5A	1.25A
Current Range	0 ÷ 2.5A	0 ÷ 1.25A
Rated Power	30W	30W
Line Regulation	± 1%	± 1%
Load Regulation	± 0.5%	± 0.5%
Voltage Tolerance [3]	± 5%	± 5%
Ripple & Noise (max.) [2]	240mV _{P-P}	240mV _{P-P}
Setup, Rise Time [4]	500ms, 50ms / 230VAC at full load	
Hold up Time (typ.)	40ms / 230VAC at full load	
INPUT		
Voltage Range	200 ÷ 240VAC	
Frequency Range	47 ÷ 63Hz	
Power Factor (typ.)	PF > 0.9 / 230VAC at full load	
Efficiency (typ.)	85%	
AC current (typ.)	0.25A / 230VAC	
Inrush current (max.)	60A / 230VAC (25°C)	
No Load Power Consumption (max.)	< 1W	
PROTECTIONS		
Over Current	Range: > 120% Type: Hiccup mode. Recovers automatically after fault condition is removed.	
Short Circuit	Type: Hiccup mode. Recovers automatically after fault condition is removed.	
Over Voltage	< 18V	< 36V
	Type: shut down output voltage. Re-power on to recovery.	

FTPC30V-E series

30W Constant Voltage LED Power Supply



WORKING ENVIRONMENT

Working Temperature	-20°C ÷ +45°C
Working Humidity	45 ÷ 85% RH non-condensing
Storage Temperature and Humidity	-30°C ÷ +70°C, 10 ÷ 95% RH non-condensing

SAFETY AND EMC REGULATIONS

Safety Standards	Compliance to EN61347-1, EN61347-2-13
Withstand Voltage	IN/OUT: 3.75kVAC
EMC Emission	Compliance to EN55015
EMC Immunity	Compliance to EN61547
Harmonic Current	Compliance to EN61000-3-2, EN61000-3-3

OTHERS


Dimensions	195 x 67.1 x 31.2mm (L x W x H)
Weight and Packing	0.14kg; 40pcs./box

EAN Code



1. All parameters NOT specially mentioned are measured at 230VAC input, rated load and 25°C of ambient temperature.
2. Ripple & noise are measured at 20MHz of bandwidth by using a 12" twisted pair-wire terminated with a 0.1µF i 47µF parallel capacitor.
3. Tolerance includes set up tolerance, line regulation and load regulation.
4. Setup and rise time is measured from 0 to 90% rated output voltage.
5. Power supply is considered as component not indented to apply by end-user. Power supply meets safety and EMC standards however the final equipment with power supply must be re-quality to comply with EMC Directives.

© MECHANICAL SPECIFICATION



PIN ASSIGNMENT

No.	Assignment	No.	Assignment
1	Input: AC/N/L	3	Output: U _{OUT} +
2	Input: AC/N/L	4	Output: U _{OUT} -